

PV 2015D Powered Enclosure



OVERVIEW

The PV 2015D is a quasi-three-way, self-powered sound reinforcement speaker system based dual 15" Sheffield® woofers and a RX™14 titanium diaphragm dynamic compression driver mounted on a Peavey® asymmetrical Quadratic Throat Waveguide™, with a coverage pattern of 100° by 50°. The PV 2015D features a Class-D power section that provides up to 800 peak available watts of power for the system, with DDT™ compression. Input jacks provided are a balanced input XLR and a 1/4" phone combination jack, with a volume control and a Contour switch for boosting lows and highs.

FEATURES

- Quasi three-way powered sound reinforcement enclosure
- Peavey exclusive dual 15" Sheffield woofers with 2-3/8" voice coil & 50 oz. magnet
- RX™14 1.4" titanium diaphragm compression driver
- 100° x 50° Quadratic Throat Waveguide technology
- Asymmetrical horn directs the sound down to the audience
- Class D powered system with up to 800W total peak available power
- Contour switch provides bass and treble lift
- Carpet-covered trapezoidal enclosure
- Steel handles and protective corners
- DDT compression/anti-clipping protection
- Full-coverage heavy-duty perforated steel grille, with powder-coat finish
- Signal input via combination female XLR and 1/4" jack, providing balanced operation
- T-Nut speaker mounting
- Heavy-duty crossover network with high-frequency driver protection
- Weight Unpacked: 81.13 lb(36.8 kg)
- Weight Packed: 85.98 lb(39 kg)
- Width Packed: 22.125"(56.1975 cm)
- Height Packed: 46.5"(118.11 cm)
- Depth Packed: 20.5"(52.07 cm)